Accessories

IMAGE	PART NUMBER	DESCRIPTION	IP RATING
	HV1437-TOP	Replacement glass to suit HV1437 & HV1438	NA
	HV350-SPK	Optional garden spike to suit: HV1494C, HV1494W and HV1494RGB	NA
	**HV1607**	• Bollard spike • High grade stainless steel • 400mm Length • Includes stainless steel base plate	NA
	HV9971	• Maintenance kit recommended for all stainless steel luminaires • Kit will clean and protect	NA
	HV9911	• Suitable Wires • 22-10AWG / 0.3247-5.26 mm^2 • Waterproof and corrosion proof-IP67. • Pre-filled non hardening silicone gel • Eliminates need for heat shrink, tape or sealants. • Can be used with 12v DC or 24v DC	IP67
	HV9912	• Suitable Wires • 22-8AWG / 0.3247-8.37 mm^2 • Waterproof and corrosion proof-IP67. • Pre-filled non hardening silicone gel • Eliminates need for heat shrink, tape or sealants. • Can be used with 12v DC or 24v DC	IP67
	HV9913	• Suitable Wires • 22-6AWG / 0.3247-13.3 mm^2 • Waterproof and corrosion proof-IP67. • Pre-filled non hardening silicone gel • Eliminates need for heat shrink, tape or sealants. • Can be used with 12v DC or 24v DC	IP67
	HV9905	• Junction Box • IP Rating: IP65	IP65

All low voltage products that specify an input of 12v or 24v DC must be used with a suitable LED driver, refer to pages 315 - 324
Lumen output measured at source. All globes supplied with fittings are non dimmable. If you require 240v dimmable globes refer to page 418 & 420