

DOT 340, 360 & 370

Highly efficient compact fluorescent downlights for single vertical lamps.



Specification

- Easy to install, including accessories
- Easy downlight removal system
- High temperature thermo plastic control gear housing
- Remote electronic control gear
- High temperature thermo plastic lamp holder enclosure
- High temperature lamp holder
- Passivated heavy gauge pressed steel mounting legs
- High purity, post anodised bright aluminium reflector
- Available with Electronic, Analogue, DSI and DALI Dimming
- UV stabilised thermoplastic moulded ceiling ring
- Large range of accessories - interchangeable after installation without removing the downlight
- Choice of reflector options and bezel colours
- Suitable for the A81 IK10 IP65 Secured access anti-vandal accessory
- Complete with 3 pin flex and plug



Quick Spec

Pierlite DOT recessed open downlight polished silver reflector and white trim, 18W, 26W, up to 42W triple CFL lamps.

Design Application


Office, boardrooms, foyers, retail, schools, TAFE's Universities, Shopping centres.

Product Codes

Code	Version	Dim (mm)	Mass (kg)
370/02/HF	1 x 26/32/42W	190 x 226	0.93
360/02/HF	1 x 26W	190 x 226	0.62
340/02/HF	1 x 18W	190 x 226	0.86


Performance

DOT 340- 18W TC-D




Reflectance		Room Index									
C	W	F	0.75	1.0	1.25	1.50	2.0	2.5	3.0	4.0	5.0
70	50	20	.42	.48	.51	.53	.57	.59	.60	.62	.63
	30		.39	.44	.48	.51	.54	.57	.58	.60	.62
	10		.36	.42	.46	.48	.52	.55	.56	.59	.60
50	50	20	.41	.47	.50	.52	.55	.57	.58	.60	.61
	30		.38	.44	.47	.50	.53	.55	.56	.58	.60
	10		.36	.41	.45	.48	.51	.53	.55	.57	.59
30	50	20	.40	.46	.49	.51	.53	.55	.56	.58	.58
	30		.38	.43	.46	.49	.52	.54	.55	.57	.58
	10		.36	.41	.45	.47	.50	.52	.54	.56	.57
0	0	0	.35	.40	.43	.45	.48	.50	.52	.53	.54

DOT 360 - 26W TC-T



Reflectance		Room Index									
C	W	F	0.75	1.0	1.25	1.50	2.0	2.5	3.0	4.0	5.0
70	50	20	.52	.58	.61	.64	.67	.69	.70	.72	.73
	30		.48	.54	.58	.61	.64	.67	.68	.70	.72
	10		.46	.52	.56	.58	.62	.65	.67	.69	.71
50	50	20	.51	.56	.60	.62	.65	.67	.68	.70	.71
	30		.48	.54	.57	.60	.63	.65	.66	.68	.69
	10		.45	.51	.55	.58	.61	.63	.65	.67	.68
30	50	20	.50	.55	.58	.61	.63	.65	.66	.67	.68
	30		.47	.53	.56	.58	.61	.63	.65	.66	.67
	10		.45	.51	.54	.57	.60	.62	.63	.65	.66
0	0	0	.44	.00	.49	.00	.53	.00	.55	.00	.58

DOT 370 - 42W TC-T/E



Reflectance		Room Index									
C	W	F	0.75	1.0	1.25	1.50	2.0	2.5	3.0	4.0	5.0
70	50	20	.50	.57	.61	.65	.69	.72	.74	.76	.78
	30		.45	.52	.57	.61	.66	.69	.71	.74	.76
	10		.42	.49	.54	.58	.63	.66	.69	.72	.75
50	50	20	.49	.55	.60	.63	.67	.70	.71	.74	.75
	30		.44	.51	.56	.60	.64	.67	.69	.72	.74
	10		.41	.48	.53	.57	.62	.65	.67	.70	.72
30	50	20	.48	.54	.58	.61	.65	.67	.69	.71	.72
	30		.44	.51	.55	.58	.63	.65	.67	.70	.71
	10		.41	.48	.53	.56	.61	.64	.66	.68	.70
0	0	0	.40	.00	.46	.00	.51	.00	.54	.00	.58

