

Split

Wall mounted luminaire with contemporary styling to suit stylish architectural space.



Robust extruded and die-cast aluminium construction with a smooth silver polyester powder coat paint finish

Specification

- Optional combinations of wide and narrow beams using reflector and optical window systems
- Supplied with a single Ceramic Metal Halide lamp, rated 35W or 70W with G12 base
- Electronic control gear in a thermally isolated housing rated for 40°C ambient operation
- Segregated IP55 lamp and gear housings ensure optimum performance
- Unique concealed mounting system allows for easy flush looking installation
- Robust extruded and die-cast aluminium construction with a smooth silver polyester powder coat paint finish
- Stainless steel exposed fasteners & metalware



Quick Spec

Pierlite Split IP55 square look, surface mounted wall light in die-cast aluminium for up or downward illumination. Tempered glass lenses, internal reflectors and integral electronic gear in the base. Smooth polyester powdercoat paint finish in silver.

Design Application

Provides both functional and accent lighting for building facades, awnings or columns.

Product Codes

Code	Version	Dim (mm)	Mass (kg)
SPLIT70NN	70W Narrow/Narrow	155 x 208 x 220	3.8
SPLIT70WN	70W Wide/Narrow	155 x 208 x 220	3.8
SPLIT70W	70W One Wide Only	155 x 208 x 220	3.8
SPLIT70WW	70W Wide/Wide	155 x 208 x 220	3.8
SPLIT35W	35W One Wide Only	155 x 208 x 220	3.8
SPLIT35NN	35W Narrow/Narrow	155 x 208 x 220	3.8
SPLIT35WN	35W Wide/Narrow	155 x 208 x 220	3.8
SPLIT35WW	35W Wide/Wide	155 x 208 x 220	3.8

Performance

SPLIT70 W 1 x CDM-T 70W G12 / 830
L.O.R. = 0.29 1 x 6600 lm

