

Sicura Wall T5

Energy efficient T5 wall mount luminaire for architectural applications.



Specification

- Extruded aluminium housing with die-cast aluminium end caps in graphite colour, polyester powder coat
- 5mm thick toughened glass is resistant to thermal shock and impact, rated IK08
- Optional fixed position or angular adjustable mounting brackets available
- Selection of T5 high output lamps with integrated electronic ballast circuits on modular gear trays
- Symmetrical reflector in high purity aluminium with anodised protection
- Also available with LED options upon request
- Silicone rubber seals ensure IP65 weather protection



Quick Spec

Disano Sicura Wall T5 surface mount linear wall washer in aluminium with IK08 5mm glass cover, rated IP65. Powdercoat paint finish and optional fixed or adjustable mounting brackets.

Design Application

Suitable for uniform floodlighting of walls, features and signage where the luminaire is sited close to the work plane.

Product Codes

Code	Version	Dim (mm)	Mass (kg)
414213-00	54W T5 Wall Mt	1546 x 140 x 104	5.8
414212-00	49W T5 Wall Mt	1246 x 140 x 104	7.0
414211-00	39W T5 Wall Mt	946 x 140 x 104	4.5
414210-00	24W T5 Wall Mt	646 x 140 x 104	3.4

Accessories

993922	Fixed Surface Mount Brackets
993923	Adjust. Surface Mount Brackets

