

# Tone

Circular surface mounted CFL luminaires with optional trim designs.



### Specification

- Vandal resistant, opal polycarbonate diffusers with UV inhibitors
- Pressure die-cast aluminium construction with polyester powder coat paint finish in RAL 9005 black
- Integral magnetic ballast circuits and internal reflectors for optimum performance
- Silicone rubber seals provide IP55 weather resistance
- Stainless steel exposed fasteners
- Optional face trims provide extra mechanical protection or light controlling feature



### Quick Spec

Pierlite Tone IP55 bulkhead wall light in pressure die cast LM6 aluminium with polyester powdercoat paint in Black RAL 9005. Integral control gear and lamps, select cover type to suit application.

### Design Application

Exterior lighting around commercial buildings, fast food outlets, shopping centres, schools and public buildings.

### Product Codes

Code	Version	Dim (mm)	Mass (kg)
TONE26203	26W PLC Open Face	265 x 105	2.5
TONE26703	26W PLC Grille Cover	265 x 105	2.5
TONE26103	26W PLC Eyelid Cover	265 x 105	2.5
TONE18702	18W PLC Grille Cover	265 x 105	2.5
TONE18202	18W PLC Open Face	265 x 105	2.5
TONE18102	18W PLC Eyelid Cover	265 x 105	2.5

### Performance

