


Tone SS

Circular semi recessed CFL luminaires featuring corrosion resistant stainless steel face trims.



Specification

- Vandal resistant, opal polycarbonate diffusers with UV inhibitors
- AISI 316 stainless steel face trims with optional designs
- Die-cast aluminium base with polyester powder coat protection
- Integral magnetic ballast circuit on a modular gear tray for easy installation
- Silicone rubber seals provide IP55 weather resistance
- Twin cable entries allow for through wiring if required
- Stainless steel exposed fasteners
- Base is semi recessed into the wall to reduce the profile height



Quick Spec

Pierlite Tone SS IP55 bulkhead wall light with LM6 aluminium base and 316 stainless steel front trim with opal polycarbonate lens, integral control gear and lamps. Select face trim to suit application.

Design Application

Exterior lighting around commercial buildings, fast food outlets and shopping centres.

Product Codes

Code	Version	Dim (mm)	Mass (kg)
TONESS18WW05	18W PLC Tri- Grille	270 x 95	3.5
TONESS26WW05	26W PLC Tri-Grille	270 x 95	3.5
TONESS26WW02	26W PLC Horizontal Grille	270 x 95	3.5
TONESS18WW02	18W PLC Horizontal Grille	270 x 95	3.5
TONESS26WW01	26W PLC Open Face	270 x 95	3.5
TONESS18WW01	18W PLC Open Face	270 x 95	3.5

Performance

