

Two Tone

Circular surface mounted CFL luminaires designed for the ambient lighting of building exteriors.



Specification

- Vandal resistant, opal polycarbonate diffuser with UV inhibitors
- Pressure die-cast aluminium construction with polyester powder coat paint finish in RAL 9005 black
- Integral magnetic control gear circuits and internal reflectors for optimum performance
- Silicone rubber seals provide IP55 weather resistance
- Stainless steel exposed fasteners
- Optional face trims provide extra mechanical protection or light controlling features



Quick Spec

Pierlite Two Tone IP55 bulkhead wall light in pressure die-cast LM6 aluminium with polyester powdercoat paint in black RAL 9005. Integral control and lamps, select face type to suit application.

Design Application

Exterior lighting around offices, fast food outlets, shopping centres, schools, universities and any public space.

Product Codes

Code	Version	Dim (mm)	Mass (kg)
TTONE226503	2 x 26W PLC Grille Cover	360 x 160	4.5
TTONE226603	2 x 26W PLC Eyelid Cover	360 x 160	4.5
TTONE226303	2 x 26W PLC Open Face	360 x 160	4.5
TTONE218603	2 x 18W PLC Eyelid Cover	360 x 160	4.5
TTONE218502	2 x 18W PLC Grille Cover	360 x 160	4.5
TTONE218302	2 x 18W PLC Open Face	360 x 160	4.5

Performance

