

Digitek Optical Fiber Simplex Patch Leads SC-APC / SC-APC Connectors

Description:

Brand Name: Digitek
 Model Number: 06LSCAPCxx.x (xx.x denotes length)
 Fiber type: Singlemode
 Insertion Loss: <0.3db
 Return Loss: >45db
 Color: Yellow

Features:

1. Price-Competitive
2. Low Insertion Loss & PDL
3. Factory-terminated and Tested
4. Fiber Type: SM OS2 9/125UM
5. Jacket Diameter: 3.0mm
6. Connector Options: SC (Green Plug)
7. Polishing Options: APC (8°)
8. Connector with Ceramic Ferrules
9. Lengths – 2, 5, 10, 20 & 50m

Applications:

1. Access Network
2. Telecom/CATV Systems
3. FTTx



Click to add text

Parameters	Standard Fiber Cable Assemblies
Fiber Type	SM OS2 9/125UM
Jacket Materials	PVC
Connector Type	SC-APC 8°
Ferrule Materials	Ceramic
Testing Wavelengths	1310±30/1550±30nm
Insertion Losss(dB) TIA/EIA-455-107	≤ 0.3dB (APC)
Return Loss(dB) TIA/EIA-455-107	≥45dB(PC/UPC) ≥55dB(APC)
Exchangeability	≤ 0.2dB
Cable Assemblies	Simplex Patch Lead
Operating Temperature (° C)	-10~ + 70
Storage Temperature (° C)	-40 ~ +85
Package	1unit/bag

*All values specified are with connectors.