

CERTECH 1 x 4 HDMI2.0 POE Splitter Extender, Includes 4 Receivers

HDMIEXTSP1-4PRO

DETAILS:

- Distribute 1 HDMI source to 4 HD displays over network cable simultaneously
- Transmitter supports one HDMI Loop-out
- Compatible with CAT6/6a/7 network cables
- The transmission distance is 30m/100ft
- The Highest resolution is up to 4K/2K@60Hz
- Support 20~60KHz IR pass back
- Support power from transmitter to receiver unit over the CAT6 cable
- Plug and play
- Wall-mounted function, easy installation



Specification	
Product Code	HDMIEXTSP1-4PRO
Technical	
Input	HDMI×1(Type A, 19 pin, female)
Output	RJ45×4
Transmission distance	30m@4K×2K@60Hz 50m@4K×2K@30Hz 60m@1080p@60Hz via CAT6
Video support	480i@60Hz, 480p@60Hz, 576i@50Hz, 576p@50Hz, 720p@50/60Hz, 1080i@50/60Hz, 1080p@50/60Hz, 4K×2K@24/25/30/60Hz
Audio format	PCM
TMDS signal	0.5~1.5Vp-p(TMDS)
DDC signal	5Vp-p(TTL)
IR passback function	Support
IR frequency Range (KHz)	Support 20~60KHz IR frequency devices
HDMI loopout	Support
HDCP	HDCP2.2
Mechanical	
Housing	Metal enclosure
Dimensions(L×W×H mm)	Splitter unit: 212.6*101.5*31 mm ; Receiver unit: 101*81.6*20.6mm
Net weight	Splitter unit: 620g ; Receiver unit:190g
Fixture	wall-mounting case with screws
Power supply	12V/3A
Power consumption	Splitter unit: <29W; Receiver unit: <6W
Operation temperaure	0~60°
Storage temperature	-20~70°
Relative humidity	20-90% (no condensation)