

PATHFINDER

3W LED EMERGENCY LUMINAIRE

SURFACE MOUNT



BLACK ALSO AVAILABLE ON REQUEST



RECESSED



240V 50Hz	5W TOTAL WATTAGE	3W NON-MTD LAMP	SMD LED		CRI >80	Ta 40°C	D40	70-130mm	AS/NZS APPROVED
--------------	------------------------	-----------------------	---------	--	------------	------------	-----	----------	--------------------

3W Pathfinder Emergency downlight is a general purpose, non-maintained LED emergency luminaire with D40/D40 classification, compliant to AS/NZS2293.

The Pathfinder luminaire incorporates an integral emergency 2 hour battery pack that permits self-powered operation during power outages.

FEATURES

- Compliant to AS/NZS 2293
- Energy efficient high output 3 watt LED
- 2-Pin flex & plug included
- Recessed or ceiling surface mount options available
- Injection moulded polycarbonate housing
- Removeable large trim ring included
- D40/D40 classification
- High density storage LiCoO₂ batteries
- IP20 rating
- 2 Hour duration period
- TA40 - maximum thermal ambient operating temperature
- Charger type: Trickle
- Charger time: 16 Hours
- Charger operation: Continuous
- Cutout: 70 to 130mm

APPLICATIONS

Commercial and interior applications, coastal environment, apartments, shopping centres, hospitality, prisons and hospitals.

CLASSIFICATION & SPACING DISTANCE

		Mounting Height in Metres								
Plane	Class	2.1	2.4	2.7	3.0	3.6	4.0	4.5	5.0	6.0
C0	D40	16.7	17.4	18.0	18.6	19.6	20.1	20.8	21.3	22.1
C90	D40	16.7	17.4	18.0	18.6	19.6	20.1	20.8	21.3	22.1

MODEL NO.	MOUNT TYPE	NON-MAINTAINED LAMP WATTAGE (W)	FITTING COLOUR	
19882/..	RECESSED	3	/05-WHITE	/06-BLACK
19886/..	SURFACE	3	/05-WHITE	
19895/..	SURFACE MOUNT BOX ONLY		/05-WHITE	

